

FD614GS1-R550

4GE+1POTS+2WIFI6(AX1500) XPON ONU



High Speed CPU



Low Power Consumption



Software Customization




Optional Shell Supply

Brief Views

FD614GS1-R550 is WiFi6 xPON VoIP Gateway ONT, it support 802.11a/b/g/n/ac/ax standards over 2.4GHz and 5GHz, max speed can up to 1500Mbps.



FD614GS1-R550 have a high reliability and provide quality of service guarantee, easy management, flexible expansion and networking. It fully meets the ITU-T and IEEE technical standards and have good compatibility with third party OLT.



Functional Feature

- In compliant with IEEE802.3ah and ITU - T G.984 standard
- Support ONU auto-discovery/Link detection/remote upgrade of software
- Support SN and LOID+Password multiple registration methods
- Support port VLAN configuration
- Support port-based rate limitation and bandwidth control
- Support port flow-control
- Support MAC address learning
- Support MAC address learning account limit
- Support VLAN transparent/tag/translate/trunk
- Support broadcasting storm resistance function
- Support igmp transparent/snooping/proxy mode
- Support Dynamic Bandwidth Allocation (DBA)
- Support AES encryption and decryption
- EMS network management based on SNMP ,convenient for maintenance
- Support power-off alarm function ,easy for link problem detection
- Support Firewall
- Support MAC address/URL filter
- Support Remote WEB/Telnet access control

Product Interface and LED



LED Definitions

Indicator		Description
PWR	Power status	On: The ONT is power on; Off: The ONT is Power off;
PON	ONT Register	On: Success to register to OLT; Blinking: In process of registering to OLT; Off:Failed to register to OLT or no normal optical signal input;
LOS	PON optical signals	On: Optical power lower than receiver sensitivity; Off: Optical in normal;
LAN1-4	LAN port status	On: Ethernet connection is normal; Blinking: Data is being transmitted through the Ethernet port; Off: Ethernet connection is not set up;
INT	Internet status indicator	On: The routed WAN Internet access service is normal. Off: The routed WAN Internet access service is abnormal.
TEL	Telephone port status	On:The connection between the TEL port and the voice server has been set up Blinking:The voice service of the TEL port is established; Off:The connection between the TEL port and the voice server is not set up.
WIFI	WIFI	Blinking:Data is being transmitted On:WIFI function Opens

Product Specification

Mechanics

Dimensions	170mm*120mm*41mm
Weight	About 300g

Hardware

User Port (LAN)		RJ-45 connector
		4* 10/100/1000Mbps adaptive Ethernet port
		Full/half duplex
		Auto MDI/MDI-X
Indicators		PWR / PON / LOS / LAN1-4 / INT / TEL / WIFI
PON Port	PON Mode	EPON: 1000BASE-PX20+ symmetric GPON: FSAN G.984.2 standard,Class B+
	PON Rate	EPON: 1.25Gbps downstream/upstream GPON: 2.488Gbps/1.244Gbps downstream/upstream
	Wavelength	Transmit: 1310nm Receiver: 1490nm

	Receiving sensitivity	EPON: -27dBm	GPON: -28dBm
	Saturated power	EPON: -3dBm	GPON: -8dBm
	Transmitting power	EPON:0~4dBm	GPON: 0.5~5dBm

WIFI

IEEE802.11b/g/n(2.4G)

IEEE802.11a/n/ac/ax(5G)

2.4G: 40Mhz bandwidth maximum rate 300Mbps

5G: 80Mhz bandwidth maximum rate 1201Mbps

Total wireless rate is 1500Mbps

2.4G EIRP:24dBm / 5 G EIRP:22dBm

User Port(POTS)

RJ-11 connector

1*accounts

SIP protocol

TDMF

G711U/G711A/G729/G722 encoding and decoding

Environment

Working temperature

0 to 40° C

Operating humidity

10% ~ 90% (Non-condensing)

Power

External 12VDC/1.5A power supply adapter

Power consumption

<18W

Copyright © Shenzhen C-Data Technology Co., Ltd. 2023. All rights reserved.

Without the prior written consent of C-DATA, any reproduction, excerpting, backup, modification, translation or any other form of commercial use of this document or any portion of this document, and in any form or by any means, to transmit the document are prohibited.